

Carbon Block Filters Data Sheet



Applications

- Removes chlorine, volatile organic compounds (VOCs), taste and odor
- Removes sediment, dirt, rust and other suspended particles
- Standalone point-of-entry or point-of-use sediment filtration
- Prefilter for domestic or commercial water filter systems

Specifications

Filter media	Bonded 100% pure coconut shell activated carbon
Minimum temperature	4.4° C / 40° F
Maximum temperature	62.8° C / 145° F
Nominal ratings	5 micron
Recommended lifespan	6 months*

* results may vary due to feed water quality

Range

MODEL NUMBER	DESCRIPTION	DIMENSIONS	RATING (NOMINAL)	CHLORINE TASTE & ODOR REDUCTION CAPACITY @ FLOW
CB1005SWE	9 7/8" Standard, White End Caps	64mm x 251mm (2.5" x 9.875")	5 micron	10,000L @ 5l/min
CB1105SWE	9 3/4" Standard, White End Caps	64mm x 248mm (2.5" x 9.75")	5 micron	10,000L @ 5l/min
CB1005JWE	10" Jumbo, White End Caps	110mm x 254mm (4.5" x 10")	5 micron	20,000L @ 5l/min
CB2005SWE	20" Standard, White End Caps	110mm x 508mm (4.5" x 20")	5 micron	40,000L @ 5l/min
CB2005JWE	20" Jumbo, White End Caps	64mm x 508mm (2.5" x 20")	5 micron	80,000L @ 5l/min

Global Water Solutions USA reserves the right to change products or specifications without notice.



Global Water Solutions USA

3165 Lakewood Ranch Blvd. | Ste. 101 | Bradenton, FL 34211-4973
www.gwsusa.com | info@gwsusa.com